



URBAN SURFACE PROTECTION
THE TOTAL SURFACE PROTECTOR

USP-501

MOSS & ALGAE REMOVER

Product Description:

USP-501 A high performance cleaner designed to remove organic and microbiological contaminants from porous surfaces such as stone, cement, tarmac etc

USP-501 is a liquid, moss & algae remover designed to clean and protect surfaces from moss and algae. The product does not contain solvents, acids or caustic soda.

Uses:

Risk-free for the user & environment.

Suitable for all substrates; can be used on metal, glass, rubber, paints, etc...

Powerful fast acting water based remover, non-corrosive and non-irritant.

Easy and quick to use, suitable for exterior and interior use, on floors & walls.

Cleans and removes contaminants from: Walls, Floors, Paths, Roofs, Boats, Monuments, and Decking, Block paving, Painted walls, Ponds.

Packaging:

1, 5, 25 and 1000 ltr Units

Technical Data:

Odour = characteristic

pH = <12

Soluble in water = soluble

S.G. = 1.09

Colour = pale yellow

VOC: Nil

Coverage = 3-5 SqM/Ltr

Directions for Use / Application:

“Always test apply on a small hidden portion of the substrate before applying.”

USP-501 moss and algae remover is supplied ready to use however on very light soiling only, dilute – 1 part product:5 parts water.

Saturate the moss and fungi (generous even application) to a dry or damp surface with a brush for thick contamination, and a garden sprayer for the thin layers. Leave for 20-30 minutes, then rinse with high pressure water jet and allow to dry.

The more porous the surface the lower the coverage rate will be.

To brighten paths and walls leave longer before removing (up to 8 hours)

To prevent future soiling, it is recommended to use a suitable protective treatment: **USP-100**.





URBAN SURFACE PROTECTION
THE TOTAL SURFACE PROTECTOR

Storage/Cleaning:

Keep in a dry place (between 5°C and 30°C).

Storage: 24 months following the production date when kept in the original unopened container.

Immediately after you have finished clean all tools and equipment with water.

Recommendations/Curing:

Wear protective gloves and glasses, and appropriate clothing whilst using the product. Do not dilute or mix with any other product, notably bleach (risks of emission of toxic chloride gas).

Do not allow the applied product to dry.

Do not apply during rain or frost and when surface and air temperature is < 5°C and > 30°C.

Health and Safety:

Respiratory Protection: Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.

Hand Protection: Wear domestic gloves.

Skin Protection: Wear protective clothing over exposed areas of skin.

Eye Protection: Wear safety goggles.

If swallowed: Do not induce vomiting. Contact a doctor or a specialist.

KEEP OUT OF THE REACH OF CHILDREN

Please refer to Material Safety Data Sheet.

Legal Notes: See USP Limited Standard Terms & Conditions.

USP is REACH compliant to EU 2015/830

Our technical department is always at your service for further information and advice.

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding regarding possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods that are beyond our control.

Urban Surface Protection Limited

Daisy Dene, Inglewhite Road, Preston, PR3 2EB

T. 01228577289

E. info@urbansurfaceprotection.co.uk

