



URBAN SURFACE PROTECTION
THE TOTAL SURFACE PROTECTOR

USP-705

RUST REMOVER

Product Description:

USP-705 is a concentrated detergent/acid pre-treatment for the removal of rust and metal oxide deposits from deteriorated surfaces.

USP-705 is ideally suited for the daily cleaning of tiled, porcelain stoneware, granite worktops and marble surfaces.

USP-705 is an aqueous-based treatment used to prepare stone and concrete surfaces before application of a finishing product.

Uses:

A powerful surface treatment that outperforms standard products, concentrated, odourless, with no need to rinse. Fast-acting, powerful degreasing and etching properties.

Water-based, non-hazardous, environmentally friendly and bio-degradable

Highly versatile: effective against all types of rust and metal oxide deposits and will remove grout blooms.

Ready & easy to use, no need to pH neutralize after rinsing and does not alter the aesthetic of the treated surface

Packaging:

1, 5, 25 and 1000 ltr Units

Technical Data:

Physical State at 20 °C:	Liquid
Appearance:	Colourless
Odour:	Characteristic
pH:	Acidic
Solubility in water:	Fully soluble
Flash Point [°C]:	Not applicable

Directions for Use / Application:

“Always test apply on a small hidden portion of the substrate before applying.”

This product is specially designed to remove rust, metal oxide deposits and clean all synthetic and stone surfaces. Shake the container well before use

To apply:

Use: Sponge or cloth and then leave it to soak, allowing 5-30 minutes to act. When immersing items, allow to soak for 20 minutes, take out the parts, brush and rinse in running water





URBAN SURFACE PROTECTION
THE TOTAL SURFACE PROTECTOR

Guidelines for use:

Apply product to the surface using a sponge, moving from bottom to top, agitate with a firm

bristle brush then wipe with a cloth or soft wipe. No rinsing required. The surface is ready to be treated or painted as soon as it has been wiped down and allowed to dry.

Storage/Cleaning:

Keep in a dry place (between 5°C and 30°C).

Storage: 24 months following the production date when kept in the original unopened container.

Immediately after you have finished clean all tools and equipment with water.

Recommendations/Curing:

USP-705 contains is a corrosive product, and it is advised to wear gloves, safety goggles and an adequate combination during the period of use

To obtain the best look and results on application, **USP-705** should be shaken before use and must be used only when the temperature of the surfaces to be treated is > 5°C

Do not apply during rainy or very hot weather.

Health and Safety:

Respiratory Protection: Under normal conditions no special respiratory protection equipment is needed.

Hand Protection: Wear protective gloves

Skin Protection: Protective clothing

Eye Protection: Safety glasses with side-shields

If Swallowed: do not induce vomiting. Contact a doctor or a specialist

KEEP OUT OF THE REACH OF CHILDREN

Please refer to Material Safety Data Sheet.

Legal Notes: See USP Limited Standard Terms & Conditions.

USP is REACH compliant to EU 2015/830

Our technical department is always at your service for further information and advice.

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding regarding possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods that are beyond our control.

Urban Surface Protection Limited

Daisy Dene, Inglewhite Road, Preston, PR3 2EB

T. 01228577289

E. info@urbansurfaceprotection.co.uk

