



URBAN SURFACE PROTECTION  
THE TOTAL SURFACE PROTECTOR

# USP-708

## GRAFFITI REMOVER

### Product Description:

**USP-708** is a solvent based, activated product for removal of graffiti from painted/ and non-painted substrates

### Uses:

Risk-free for the user, suitable for most substrates; can be used on metal, glass, rubber, paints, etc (always check with trial area prior to use)

Powerful fast acting based remover, non-corrosive and non-irritant.

Easy and quick to use, suitable for exterior and interior use on floors & walls.

### Packaging:

1, 5, 25 and 1000 ltr Units

### Physical Properties:

State:	Liquid	
Colour:	Colourless	
Odour:	Sweet-smelling	
Evaporation rate:	Slow	
Solubility in water:	Slightly soluble	
Also soluble in:	Most organic solvents.	
Viscosity:	Non-viscous	
Boiling point°C:	100	Flash point°C: >93oC
pH:	4	
VOC g/l:	559	
Coverage:	Dependant on substrate	

### Directions for Use / Application:

“Always test apply on a small hidden portion of the substrate before applying.”

**USP-708** Testing first on the surface is essential to establish correct dwell time to ensure underneath substrate is not affected. Apply the product to a dry surface by brush, spray or broom onto the contaminated area. Leave for the period predetermined in the pre-test. Agitate with a brush and remove graffiti with sponges or power washer. Wash surface with water and clean off any remaining residues





URBAN SURFACE PROTECTION  
THE TOTAL SURFACE PROTECTOR

---

Benefits of **USP-708** are;

Safer

Easy to use

Fast Acting

Low Fumes

Versatile

To prevent future soiling, it is recommended to use a suitable protective treatment: **USP-100**.

---

### Storage/Cleaning

Keep in a dry place (between 5°C and 30°C).

Storage: 24 months following the production date when kept in the original unopened container.

Immediately after you have finished clean all tools and equipment with water.

---

### Recommendations/Curing:

Wear protective gloves and glasses, and appropriate clothing whilst using the product. Do not dilute or mix with any other product.

Do not allow the applied product to dry.

Do not apply during rain or frost and when surface and air temperature is < 5°C and > 30°C.

---

### Health and Safety:

Respiratory Protection: Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.

Hand Protection: Wear domestic gloves.

Skin Protection: Wear protective clothing over exposed areas of skin.

Eye Protection: Wear safety goggles.

If swallowed: Do not induce vomiting. Contact a doctor or a specialist.

**KEEP OUT OF THE REACH OF CHILDREN**

Please refer to Material Safety Data Sheet.

Legal Notes: See USP Limited Standard Terms & Conditions.

USP is REACH compliant to EU 2015/830

---

**Our technical department is always at your service for further information and advice.**

Our technical advice and recommendations given verbally, in writing or by trials are believed to be correct. They are neither binding regarding possible rights of third parties nor do they exempt you from your task of examining the suitability of our products for the intended use. We cannot accept any responsibility for application and processing methods that are beyond our control.

**Urban Surface Protection Limited**

**Daisy Dene, Inglewhite Road, Preston, PR3 2EB**

**T. 01228577289**

**E. [info@urbansurfaceprotection.co.uk](mailto:info@urbansurfaceprotection.co.uk)**

